Zoning District	Minimum Lot Size (sf)			Minimum Density (dwelling units per acre)			Minimum Lot width (ft)	Minimum setback (ft)			Maximum Building Height (ft)	Maximum Impervious Surface	
	Without public water & sewer	Without public sewer	With public water & sewer	Without public water & sewer	Without public sewer	With public water and sewer		Front	Side yard	Street side yard	Rear		
R-20	32,670	21,780	10,890	1	3/4	1/4	100	$30^{4}$	10	15	25	35	50%
RA-20	32,670	21,780	10,890	1	3/4	1/2	100	$30^{4}$	10	15	25	35	50%
R-15	32,670	21,780	10,890	1	3/4	1/2	100	$30^{4}$	10	15	25	35	50%
O-I	10,000	10,000	10,000	-	-	-	80	$40^{4}$	15	15	20	35	40%
N-B	10,000	10,000	10,000	-	-	-	100	$40^{4}$	15	20	30	35 <sup>1</sup>	40%
Н-В	-	-	-	-	-	-	100	50 <sup>4</sup>	15	20	30	50 <sup>2</sup>	40%
G-M	43.560	43,560	43.560	-	-	-	200	50 <sup>4</sup>	$30^{3}$	$30^{3}$	$30^{3}$	$50^{2}$	40%

Structures may exceed a height of 35 feet by increasing the setback line one foot for each two feet of rise above 35 feet.

Structures may exceed a height of 50 feet by increasing the setback line one foot for each two feet of rise above 50 feet.

An additional 15 feet is required if the lot abuts a residential district.

In the absence of a dedicated right-of-way, it shall be deemed there is a 45 foot right-of-way, in which the existing street is centered. (Ord. passed 4-17-12)